



**Paslanmaz Çelik Kaynak Boyunlu Flanşlar RF 1500 lbs**  
**ASTM A182 / ANSI B16.5 normunda**

BORU ÖLÇÜSÜ	FLANŞ ÖLÇÜLERİ							VİDALAMA			TEOR. AĞIRLIK kg/item
	D	b	g	m	d1	h	s	nr.	L	k	
1/2" Sch 80 S XS	120,70	22,40	34,90	38,10	21,30	60,50	3,73	4	22,50	82,50	2,10
1/2" Sch 160	120,70	22,40	34,90	38,10	21,30	60,50	4,75	4	22,50	82,50	2,10
3/4" Sch 80 S XS	130,00	25,40	42,90	44,50	26,67	69,90	3,91	4	22,5	88,90	2,70
1" Sch 40 S STD	149,40	28,40	50,80	52,30	33,40	73,20	3,38	4	25,4	101,60	3,90
1" Sch 80 S XS	149,40	28,40	50,80	52,30	33,40	73,20	4,55	4	25,4	101,60	3,90
1" Sch 160	149,40	28,40	50,80	52,30	33,40	73,20	6,35	4	25,4	101,60	3,90
1.1/2" Sch 80 S XS	177,80	31,80	73,00	69,90	48,30	82,30	5,08	4	28,5	123,80	6,20
2" Sch 40 S STD	215,90	38,10	92,10	104,60	60,30	101,60	3,91	8	25,5	165,10	11,30
2" Sch 80 S XS	215,90	38,10	92,10	104,60	60,30	101,60	5,54	8	25,5	165,10	11,30
4" Sch 80 S XS	311,20	53,80	157,20	162,10	114,30	124,00	8,56	8	35	241,30	31,80
4" Sch 160	311,20	53,80	157,20	162,10	114,30	124,00	13,49	8	35	241,30	31,80