



## Paslanmaz Çelik KEPLER

ASTM A403, A815 / ANSI B16.9 normunda

	DIŞ ÇAP		ET KALINLIĞI		TEOR. AĞIRLIK
	D		S	h	
İNÇ	mm	SCH	mm	mm	kg/item
1/2"	21,34	10s	2,11	25,40	0,03
		40s	2,77	25,40	0,04
3/4"	26,67	10s	2,11	25,40	0,04
		40s	2,87	25,40	0,05
1"	33,40	10s	2,77	38,10	0,09
		40s	3,38	38,10	0,11
1.1/4"	42,16	10s	2,77	38,10	0,11
		40s	3,56	38,10	0,14
1.1/2"	48,26	10s	2,77	38,10	0,13
		40s	3,68	38,10	0,17
2"	60,33	10s	2,77	38,10	0,17
		40s	3,91	38,10	0,23
2.1/2"	73,03	10s	3,05	38,10	0,23
		40s	5,16	38,10	0,39
3"	88,90	10s	3,05	50,80	0,37
		40s	5,49	50,80	0,66
4"	114,30	10s	3,05	63,50	0,59
		40s	6,02	63,50	1,17
5"	141,30	10s	3,40	76,20	0,99
		40s	6,55	76,20	1,91
6"	168,28	10s	3,40	88,90	1,39
		40s	7,11	88,90	2,90
8"	219,08	10s	3,76	101,60	2,38
		40s	8,18	101,60	5,19
10"	273,05	10s	4,19	127,00	4,14
		40s	9,27	127,00	9,15
12"	323,85	10s	4,75	152,40	6,39
		40s	9,53	152,40	13,30

14"	355,60	10s	4,78	165,10	7,98
16"	406,40	10s	4,78	177,80	10,00
20"	508,00	10s	5,56	228,90	18,50
24"	609,00	10s	6,35	266,70	30,10