



Spesifikasyon

Standart:

ASTM

A249/A269/A270/A213(TP304/304L, TP316/316L)

JIS G3447/G3463(SUS304TBS, 304LTBS, SUS316TBS, 316LTBS)

CNS 6668/7383(304/A304LTBS, 316/A316LTBS)

AS 1528.1(304/304L, 316/316L)

Dış Çap : 12.7~114.3mm

Duvar Kalınlığı : 1.20~2.11mm

Üretim Metodu : TIG veya TIG +
Plazma veya Lazer veya Dikişsiz

ASTM A249/A269/A270/A213, JIS G3447/G3463, CNS
6668/7383, AS 1528.1

Kalınlık		Dış Çap													
		in.													
		1/2	5/8	3/4	7/8	1	1 1/4	-	1 1/2	2	2 1/2	3	3 1/2	4	4 1/2
mm	Gauge	12.7	15.9	19	22.2	25.4 (25)	31.8 (32)	35	38.1 (38)	50.8 (51)	63.5	76.2	88.9	101.6	114.3
1.20/1.25	-18	*	*	*	*	*	*	*	*	*	*	-	-	-	-
1.50	-	*	*	*	*	*	*	*	*	*	*	*	*	*	-
1.60/1.65	-16	*	*	*	*	*	*	*	*	*	*	*	*	*	-
2.00	-	*	*	*	*	*	*	*	*	*	*	*	*	*	-
2.11	14	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Not		(1)* : Ürün Özelliği ASTM A269													