



Sınıf : TP304/304L, TP316/316L
 Standart : ASTM A312/A358/A778,
 ASME B36.19M, ASME B36.10M
 Dış Çap : 1/4"~84"
 Duvar Kalınlığı : SCH-5S, SCH-10S,
 SCH-40S, SCH-80S, SCH-5, SCH-
 10, SCH-20, STD, XS
 Üretim Metodu : TIG veya TIG +
 Plazma veya Lazer veya Dikişsiz

ASTM A312/A358/A778, ASME B36.19M/ASME
 B36.10M

Nominal Çap NPS	Dış Çap (mm)	Nominal Duvar Kalınlığı (mm)								
		ASME B36.19M				ASME B36.10M				
		SCH-5S	SCH-10S	SCH-40S	SCH-80S	SCH-5	SCH-10	SCH-20	STD	XS
1/4	13.72	-	1.65	2.24	3.02	-	1.65	-	2.24	3.02
3/8	17.15	-	1.65	2.31	3.20	-	1.65	-	2.31	3.20
1/2	21.34	1.65	2.11	2.77	3.73	1.65	2.11	-	2.77	3.73
3/4	26.67	1.65	2.11	2.87	3.91	1.65	2.11	-	2.87	3.91
1	33.40	1.65	2.77	3.38	4.55	1.65	2.77	-	3.38	4.55
1 1/4	42.16	1.65	2.77	3.56	4.85	1.65	2.77	-	3.56	4.85
1 1/2	48.26	1.65	2.77	3.68	5.08	1.65	2.77	-	3.68	5.08
2	60.33	1.65	2.77	3.91	5.54	1.65	2.77	-	3.91	5.54
2 1/2	73.03	2.11	3.05	5.16	7.01	2.11	3.05	-	5.16	7.01
3	88.90	2.11	3.05	5.49	7.62	2.11	3.05	-	5.49	7.62
3 1/2	101.60	2.11	3.05	5.74	8.08	2.11	3.05	-	5.74	8.08
4	114.30	2.11	3.05	6.02	8.56	2.11	3.05	-	6.02	8.56
5	141.30	2.77	3.40	6.55	9.53	2.77	3.40	-	6.55	9.53
6	168.28	2.77	3.40	7.11	10.97	2.77	3.40	-	7.11	10.97
8	219.08	2.77	3.76	8.18	12.70	2.77	3.76	6.35	8.18	12.70
10	273.05	3.40	4.19	9.27	12.70	3.40	4.19	6.35	9.27	12.70
12	323.85	3.96	4.57	9.53	12.70	3.96	4.57	6.35	9.53	12.70
14	355.60	3.96	4.78	9.53	12.70	3.96	6.35	7.92	9.53	12.70
16	406.40	4.19	4.78	9.53	12.70	4.19	6.35	7.92	9.53	12.70
18	457.20	4.19	4.78	9.53	12.70	4.19	6.35	7.92	9.53	12.70
20	508.00	4.78	5.54	9.53	12.70	4.78	6.35	9.53	9.53	12.70
22	558.80	4.78	5.54	-	-	4.78	6.35	9.53	9.53	12.70

24	609.60	5.54	6.35	9.53	12.70	5.54	6.35	9.53	9.53	12.70
26	660.40	-	-	-	-	-	7.92	12.70	9.53	12.70
28	711.20	-	-	-	-	-	7.92	12.70	9.53	12.70
30	762.00	6.35	7.92	-	-	6.35	7.92	12.70	9.53	12.70
32	812.80	Thickness : 6.35~30mm								
84	2133.60									
Not	(1)Kütle Deęeri Hesaplama Formülü (kg/m) : 304/L[W=0.02491t(D-t)], 316/L[W=0.02507t(D-t)]									